

## 2T TC W3 MARINE

It is specially produced to provide high performance in two-stroke engines and other small engines, for 2-stroke engines lubricated with premix, direct injection or carburetor: EVINRUDE, JOHNSON, MARINER, MERCURY, SEAGULL, SELVA, SUZUKI, TOHATSU, YAMAHA etc. engines also 2 For stroke Jet engine: KAWASAKI JET SKI,; KAWASAKI, YAMAHA, POLARIS, BRP etc. Designed to meet the requirements of engines. It is suitable for all kinds of gasoline fuel , especially leaded or unleaded gasoline, ethanol or non-ethanol , biofuels.

### Features and Benefits

- Provides full protection against soot formation.
- It lubricates the engine parts perfectly and ensures a fast and reliable start-up.
- It provides good compression with excellent cleaning properties.

### Technical specifications

TEST	METHO D	VALUES
Kinematic Viscosity (100° C)	ASTM D 445	7.5-11.3 cSt
Viscosity Index	ASTM D 2270	Min.110
Flash Point	ASTM D 92	Min.210°C
Pour Point	ASTM D97	Max .(-25°C)

### Approvals and Specifications

- ◆ API TSC 4
- ◆ NMMA TC-W / TC-W3 / TC-WII

### Storage Information

- ☞ Packaging; It should be stored in covered areas with tightly closed lids.
- ☞ It should not be exposed to the direct effects of solar heat and heat sources.
- ☞ exceed 60°C . It should be stored with a maximum of two pallets on top of each other.
- ☞ For more information, refer to the Material Safety Data Sheet (MSDS).