

### ARMA ELEVATOR OIL 90W GL-1

It is a special gear oil formulated from mineral base oils obtained from modern refining processes and high-quality additives. They are gear oils produced to be used in automotive gearboxes operating at normal load and speed, where there is no excessive pressure, and where API GL-1 level oil is recommended.

#### Features and Benefits

- It protects gears against wear when operating under light conditions and without excessive pressure.
- Prevents rust and corrosion.
- It ensures the protection of the oil film by preventing foam formation.
- Does not damage sealing elements

#### Technical specifications

TEST	METHOD	VALUES
Kinematic Viscosity (100° C)	ASTM D 445	13.5-18.5 cSt
Viscosity Index	ASTM D 2270	Min.92
Flash Point	ASTM D 92	Min.220°C
Pour Point	ASTM D97	Max .(-18°C)

#### Approvals and Specifications

- ◆ API GL-5/GL-4
- ◆ MAN 342 M-1
- ◆ MAN 342M-2
- ◆ SAE J2360
- ◆ Volvo 1273.10
- ◆ Scania STO 1:0
- ◆ Industrial
- ◆ ZF 05A/07A/08/12A/12E/16B-D/17B/19B/21A

#### Storage Information

- ☞ Packaging: It should be stored in covered areas with tightly closed lids. It should not be exposed to the direct effects of solar heat and heat sources.
- ☞ exceed 60°C . It should be stored with a maximum of two pallets on top of each other. For more information, refer to the Material Safety Data Sheet (MSDS).