

HYDRAULIC BRAKE DOT-3

HYDRAULIC BRAKE OIL

It is a synthetic brake and clutch hydraulic fluid that provides excellent performance and increased braking safety at different temperatures. It shows high performance even at extreme temperatures caused by friction in brake systems. It is a synthetic brake fluid developed for the brake and clutch systems of all automobiles and motorcycles.

Features and Benefits

- Provides good protection against wear.
- Provides thermal and oxidation stability.
- Helps keep engines clean for smoother operation.
- It helps extend engine life.

Approvals and Specifications

- ◆ SAE J1703
- ◆ JIS K 2233
- ◆ FMVSS 116 DOT 3
- ◆ ISO 4925

Storage Information

- ☞ Packaging; It should be stored in covered areas with tightly closed lids.
- ☞ It should not be exposed to the direct effects of solar heat and heat sources.
- ☞ exceed 60°C . It should be stored with a maximum of two pallets on top of each other.
- ☞ For more information, refer to the Material Safety Data Sheet (MSDS).

Technical specifications

TEST	METHOD	VALUES
Kinematic Viscosity (100° C)	ASTM D 445	MIN.1.5 cSt
Density 15° C	ASTM D 4052	1.026-1.085 g/cm ³
Boiling point	ASTM D 1120	Min.240°C
pH	ASTM D 1287	7.0-9.4