

KORAL 2T TC

It is a mineral-based motorcycle oil with special additives, specially produced to provide high performance in two-stroke engines and other small engines. It is used in air or water-cooled engines, motorcycles, lawn mowers and agricultural equipment. The fuel/oil mixture ratio should be determined according to the engine manufacturer's recommendation.

Features and Benefits

- ☑ Provides full protection against soot formation.
- ☑ It lubricates the engine parts perfectly and ensures a fast and reliable start-up.
- ☑ It provides good compression with excellent cleaning properties.

Technical specifications

TEST	METHOD	VALUES
Kinematic Viscosity (100° C)	ASTM D 445	7.5-11.3 cSt
Viscosity Index	ASTM D 2270	Min.110
Flash Point	ASTM D 92	Min.210°C
Pour Point	ASTM D97	Max .(-25°C)

Approvals and Specifications

- ◆ API TR
- ◆ JASO FC
- ◆ TISI 1040
- ◆ ISO EGC & EGD

Storage Information

- ☞ Packaging; It should be stored in covered areas with tightly closed lids.
- ☞ It should not be exposed to the direct effects of solar heat and heat sources.
- ☞ exceed 60°C . It should be stored with a maximum of two pallets on top of each other.
- ☞ For more information, refer to the Material Safety Data Sheet (MSDS).