

PREMIUM 5W30 SN/CF

It is a low viscosity, high stability engine oil produced as a result of the perfect blend of new generation additives and fully synthetic oils. It is recommended for all types of high-performance modern vehicles, passenger cars, gasoline engines with multi-point fuel injection, SUVs and Off-roads .

Features and Benefits

- It significantly prevents friction losses and deposit formation in the engine and provides resistance to wear.
- In addition to its excellent lubrication and anti-corrosion properties in a wide temperature range, it provides superior and long-lasting engine protection thanks to its formula developed with anti-wear technology.

Technical specifications

TEST	METHOD	VALUES
Kinematic Viscosity (100° C)	ASTM D 445	9.3-12.5 cSt
Viscosity Index	ASTM D 2270	Min.155
Flash Point	ASTM D 92	Min.200°C
Pour Point	ASTM D97	Max .(-35°C)

Approvals and Specifications

- ◆ API SN/ API SL / API CF
- ◆ ACEA A3/B3/B4
- ◆ MB-Approval229.5
- ◆ MB-Approval229.3
- ◆ Peugeot/ Citroen B71 2296
- ◆ Volkswagen VW50500
- ◆ Volkswagen VW50200
- ◆ Renault RN0710
- ◆ Renault RN0700
- ◆ BMW Longlife-01
- ◆ Porsche A40
- ◆ Opel GM-LL-B-025
- ◆ Opel GM-LL-A-025
- ◆ FORD WSS M2C 913 D
- ◆ LAND ROVER JAGUAR LAND ROVER STJLR.03.5003
- ◆ AVTOVAZ (LADA cars)

Storage Information

- ☞ Packaging; It should be stored in covered areas with tightly closed lids.
- ☞ It should not be exposed to the direct effects of solar heat and heat sources.
- ☞ exceed 60°C . It should be stored with a maximum of two pallets on top of each other.
- ☞ For more information, refer to the Material Safety Data Sheet (MSDS).