

### PREMIUM 5W30 SN C3 DPF

It is an engine oil reinforced with synthetic-based quality additive packages developed to meet the performance requirements of new generation engines. It is manufactured to be fully compatible with the latest diesel particulate filters (DPF) and catalytic converters found in gasoline vehicles. It is especially recommended for gasoline or diesel passenger and light commercial vehicles used in stop-and-go heavy city traffic.

#### Features and Benefits

- ✓ It significantly prevents friction losses and deposit formation in the engine and provides resistance to wear.
- ✓ In addition to its excellent lubrication and anti-corrosion properties in a wide temperature range, it provides superior and long-lasting engine protection thanks to its formula developed with anti-wear technology.

#### Technical specifications

TEST	METHOD	VALUES
Kinematic Viscosity (100° C)	ASTM D 445	9.3-12.5 cSt
Viscosity Index	ASTM D 2270	Min.150
Flash Point	ASTM D 92	Min.210°C
Pour Point	ASTM D97	Max .(-36°C)

#### Approvals and Specifications

- ◆ API SN/SM/SL
- ◆ API C.F.
- ◆ ACEA C3/C2-16
- ◆ MB- Approval 229.51, 229.31
- ◆ Volkswagen VW50700, VW50400
- ◆ Porsche C30

#### Storage Information

- ☞ Packaging; It should be stored in covered areas with tightly closed lids.
- ☞ It should not be exposed to the direct effects of solar heat and heat sources.
- ☞ exceed 60°C . It should be stored with a maximum of two pallets on top of each other.
- ☞ For more information, refer to the Material Safety Data Sheet (MSDS).