

PROFESSIONAL 15W40 CF-4/SJ

ENGINE OIL

It is a diesel engine oil reinforced with superior quality base oils and high additives. It is an engine oil that can be used safely in all seasons for automobiles and light commercial vehicles. It is especially suitable for passenger vehicles that operate under difficult conditions and experience frequent stops and starts. It can also be used safely in the lubrication of minibuses, pickup trucks, other four-stroke engines and other work machines. It can also be used safely in vehicles running on fuels such as gasoline and LPG.

Features and Benefits

- ✓ It significantly prevents friction losses and deposit formation in the engine and provides resistance to wear.
- ✓ Superior and long - lasting properties thanks to its formula developed with anti - wear technology as well as excellent lubrication and corrosion prevention properties in a wide temperature range. Provides long - lasting engine protection.

Technical specifications

TEST	METHOD	VALUES
Kinematic Viscosity (100° C)	ASTM D 445	12.5-16.3 cSt
Viscosity Index	ASTM D 2270	Min.120
Flash Point	ASTM D 92	Min.230°C
Pour Point	ASTM D97	Max .(-24°C)

Approvals and Specifications

- ◆ API CF-4/CF-API SJ/SL
- ◆ ACEA B2-ACEA E3/E7
- ◆ MB-Approval 228.3
- ◆ VOLVO VDS-3
- ◆ Cummins CES 20072
- ◆ Mack EO-N/ Mack EO-M
- ◆ MAN M 3275-1
- ◆ RENAULT TRUCKS RD-2
- ◆ RENAULT TRUCKS RLD
- ◆ Caterpillar ECF-2
- ◆ Cummins CES 20077
- ◆ Ford WSS-M2C171-D
- ◆ Detroit Fluids Specification 93K215

Storage Information

- ☞ Packaging: It should be stored in covered areas with tightly closed lids.
- ☞ It should not be exposed to the direct effects of solar heat and heat sources.
- ☞ exceed 60°C . It should be stored with a maximum of two pallets on top of each other.
- ☞ For more information, refer to the Material Safety Data Sheet (MSDS).