

## PROFESSIONAL 15W40 CI-4/SL

## ENGINE OIL

reinforced with superior quality base oils and extra additives, developed to be used in new generation diesel engines operating under severe conditions . It is recommended for use in vehicles with diesel turbocharged engines such as trucks, buses and construction equipment.

### Features and Benefits

- ☑ It significantly prevents friction losses and deposit formation in the engine and provides resistance to wear.
- ☑ Superior and long - lasting properties thanks to its formula developed with anti - wear technology as well as excellent lubrication and corrosion prevention properties in a wide temperature range. Provides long - lasting engine protection.

### Technical specifications

TEST	METHOD	VALUES
Kinematic Viscosity (100° C)	ASTM D 445	12.5-16.3 cSt
Viscosity Index	ASTM D 2270	Min.120
Flash Point	ASTM D 92	Min.230°C
Pour Point	ASTM D97	Max .(-27°C)

### Approvals and Specifications

- ◆ API CI-4/SL
- ◆ ACEA E7
- ◆ DEUTZ DQC III-10
- ◆ MACK EO-N
- ◆ MB-APPROVAL 228.3
- ◆ RENAULT VI RLD-2
- ◆ VOLVO VDS-3 PERFORMANCES
- ◆ CAT ECF-2
- ◆ CUMMINS CES 20078/77/76
- ◆ GLOBAL DHD-1
- ◆ MAN M 3275-1
- ◆ MTU DDC TYPE 2

### Storage Information

- ☞ Packaging; It should be stored in covered areas with tightly closed lids.
- ☞ It should not be exposed to the direct effects of solar heat and heat sources.
- ☞ exceed 60°C . It should be stored with a maximum of two pallets on top of each other.
- ☞ For more information, refer to the Material Safety Data Sheet (MSDS).