

PROFESSIONAL TRACTOR OIL 428

It is an extra high performance, multi-purpose tractor oil designed to meet the requirements of hydraulic and transmission parts manufacturers. Designed to maximize the performance of agricultural and commercial tractors.

Features and Benefits

- ✓ Thanks to its high viscosity index, it performs effectively even under very cold weather conditions.
- ✓ It ensures high efficiency and quiet operation of the brake system with its friction modifier additive.
- ✓ With its specially developed formula, it provides a long service life by keeping rust, corrosion and foam formation under control.
- ✓ Thanks to its high thermal and oxidation stability, it prevents deposit formation and increases operating efficiency.

Technical specifications

TEST	METHOD	VALUE
ISO GARD		10W30
Kinematic Viscosity (100° C)	ASTM D 445	9.3-12.5 cSt
Viscosity Index	ASTM D 2270	Min.140
Flash Point	ASTM D 92	Min.220°C
Pour Point	ASTM D97	Max .(-36°C)

TRACTOR TRANSMISSION OIL

Approvals and Specifications

- ◆ API GL-4
- ◆ VOLVO WB-101
- ◆ ZF TE-ML 05F
- ◆ ZF TE-ML 06K
- ◆ ZF TE-ML 17E
- ◆ Caterpillar TO-2
- ◆ CNH MAT 3540
- ◆ Denison UTTO/THF
- ◆ FORD NH FNHA-2-C-201.00
- ◆ JICASE AD 1209
- ◆ RENAULT AGRICULTURE (M1145)
- ◆ ZF TE-ML 21F
- ◆ MASSEY FERGUSON CMS M1145
- ◆ Allison C-4
- ◆ API GL-4
- ◆ Caterpillar TO-2
- ◆ ZF TE-ML 03E

Storage Information

- ✎ Packaging; It should be stored in covered areas with tightly closed lids.
- ✎ It should not be exposed to the direct effects of solar heat and heat sources.
- ✎ exceed 60°C . It should be stored with a maximum of two pallets on top of each other.
- ✎ For more information, refer to the Material Safety Data Sheet (MSDS).