

TRANSMISSION ATF DEXRON III

ATF III is recommended for many passenger and commercial vehicle automatic transmissions. It provides excellent grip and protection for many years with its zinc-free additive technology that has stable viscosity and significantly reduces friction. It is also suitable for power steering systems, hydraulic applications and some manual transmissions where automatic transmission fluid is specified.

Features and Benefits

- ✓ It minimizes friction in wide operating temperature ranges and provides perfect operation during gear changes.
- ✓ Advanced additives protect against corrosion, oxidation, foaming and deposits.
- ✓ Its high viscosity index provides excellent performance under all conditions and minimizes friction .

Technical specifications

TEST	METHOD	VALUES
Kinematic Viscosity (100° C)	ASTM D 445	7.2-9.4 cSt
Viscosity Index	ASTM D 2270	Min.150
Flash Point	ASTM D 92	Min.215°C
Pour Point	ASTM D97	Max .(-36°C)

Approvals and Specifications

- ◆ GM Dexron III H,
- ◆ Ford Mercon ,
- ◆ Allison C4,
- ◆ Volvo 97341,
- ◆ TES 389,
- ◆ MAN 339 Type V1/Z1,
- ◆ MBAapproval 236.1 ,
- ◆ MB Approval 236.9,
- ◆ Voith 55.6335,
- ◆ ZF TE ML-03D-04D-14A-17C

Storage Information

- ☞ Packaging; It should be stored in covered areas with tightly closed lids.
- ☞ It should not be exposed to the direct effects of solar heat and heat sources.
- ☞ exceed 60°C . It should be stored with a maximum of two pallets on top of each other.
- ☞ For more information, refer to the Material Safety Data Sheet (MSDS).