

TRANSMISSION ATF DEXRON II

It is an automatic transmission and steering oil with a high viscosity index, formulated with special package additives. It is used in steering gears, automatic transmissions and transmissions of passenger cars and heavy vehicles and, if recommended, in mechanisms with hydraulic systems.

Features and Benefits

- ☑ It minimizes friction in wide operating temperature ranges and provides perfect operation during gear changes.
- ☑ Advanced additives protect against corrosion, oxidation, foaming and deposits.
- ☑ Its high viscosity index provides excellent performance under all conditions and minimizes friction.

Technical specifications

TEST	METHOD	VALUES
Kinematic Viscosity (100° C)	ASTM D 445	7.2-9.4 cSt
Viscosity Index	ASTM D 2270	Min.150
Flash Point	ASTM D 92	Min.215°C
Pour Point	ASTM D97	Max .(-36°C)

Approvals and Specifications

- ◆ GM Dexron II,
- ◆ GM Allison C4,
- ◆ MB- Approval 236.1,
- ◆ MAN 339 Type V1,
- ◆ Voith DIWA G607
- ◆ ZF TE ML-02F/03D
- ◆ ZF TE ML-04D/14A/17C

Storage Information

- ☞ Packaging; It should be stored in covered areas with tightly closed lids.
- ☞ effects of solar heat and heat sources .
- ☞ exceed 60°C . It should be stored with a maximum of two pallets on top of each other.
- ☞ For more information, refer to the Material Safety Data Sheet (MSDS).