

TRANSMISSION ATF DEXRON CVT

It is a high performance transmission fluid specially designed for Continuously Variable Transmission (CVT) gearbox type. Designed for use in a wide range of vehicles with CVT transmissions using chain-pulley or belt-pulley. Not recommended for hybrid vehicles suitable for CVT devices. Always refer to the vehicle's owner's manual or manual before use.

Features and Benefits

- It minimizes friction in wide operating temperature ranges and provides perfect operation during gear changes.
- Advanced additives protect against corrosion, oxidation, foaming and deposits.
- Its high viscosity index provides excellent performance under all conditions and minimizes friction .

Technical specifications

TEST	METHOD	VALUES
Kinematic Viscosity (100° C)	ASTM D 445	7.2-9.4 cSt
Viscosity Index	ASTM D 2270	Min.170
Flash Point	ASTM D 92	Min.200°C
Pour Point	ASTM D97	Max .(-42°C)

Approvals and Specifications

- ◆ Audi Multitronic - BMW Mini Cooper EZL 799/799A Daihatsu AMMIX CVTF DFE
- ◆ Daihatsu AMMIX CVT Fluid DC- Daihatsu AMMIX CVT Fluid DFC- Daihatsu Fluid TC
- ◆ Dodge/Jeep/ ChryslerNS Dodge/Chrysler/Jeep/ Mopar CVT+ 4 - GM/ Saturn DEX-CVT
- ◆ Honda HMMF (without starting clutch) - Honda HCF2 - Honda Z-1 (CVT model, without starting clutch , not SFU for 2001-2007 Honda Fit & Jazz)
- ◆ - Hyundai/Kia CVT-J 1 - Hyundai/Kia SP III (CVT model) - Idemitsu CVTS-EX1 - Mazda JWS 3320
- ◆ Mini Cooper EZL 799/EZL 799A/ZF CVT V 1 - Mitsubishi CVTF-J1 (MMC Diaqueen CVT Fluid J1)
- ◆ Mitsubishi CVTF-J4 and -J4+ (MMC Diaqueen CVT Fluid J4 and J4+)
- ◆ Mitsubishi (Diaqueen) SP-III (CVT model only) - Nissan NS-1, -2, -3 - Punch CVT - Shell Green 1V
- ◆ Subaru iCVT - Subaru iCVT FG - Subaru ECVT - Subaru Lineartronic chain CVT and CVT II Fluid
- ◆ Subaru Lineartronic High Torque (HT) CVT Fluid - Subaru NS-2 - Suzuki CVTF TC - Suzuki CVTF 3320
- ◆ Suzuki NS- 2 - Suzuki CVT Green 1 & 2 - Suzuki CVT Green 1V - Toyota CVTF TC - Toyota CVTF FE
- ◆ VW/Audi TL 521 16 (G 052 516) - VW/Audi TL 521 80 (G 052 180 A2)

Storage Information

- ☞ Packaging; It should be stored in covered areas with tightly closed lids. It should not be exposed to the direct effects of solar heat and heat sources.
- ☞ exceed 60°C . It should be stored with a maximum of two pallets on top of each other. For more information, refer to the Material Safety Data Sheet (MSDS).