

KORAL 4T 20W40 SL

It is a motorcycle oil obtained using quality mineral base oils and superior performance additives. It is used in all seasons in four-stroke, high-performance, air or water-cooled motorcycles. It also meets API SL and/or JASO MA2 standard recommendations and is suitable for European and Japanese manufactured motorcycles.

Features and Benefits

- ✓ By constantly preventing dirt and sludge formation, it works harder than other conventional engine oils and reduces engine noise.
- ✓ This product meets the requirements of most motorcycle manufacturers and is suitable for use in both air-cooled and liquid-cooled 4-stroke motorcycle engines, naturally aspirated or turbocharged engines, engines adapted to all-season operation and vehicles equipped with catalytic converters.

Technical specifications

| TEST | METHOD | VALUES |
|------------------------------|-------------|---------------|
| Kinematic Viscosity (100° C) | ASTM D 445 | 12.5-16.3 cSt |
| Viscosity Index | ASTM D 2270 | Min.125 |
| Flash Point | ASTM D 92 | Min.230°C |
| Pour Point | ASTM D97 | Max .(-24°C) |

MOTORCYCLE OIL

Approvals and Specifications

- ◆ API SL/SJ/SG
- ◆ JASO MA (T903:2011)
- ◆ JASO MA2 (T903:2011)

Storage Information

- ☞ Packaging; It should be stored in covered areas with tightly closed lids.
- ☞ It should not be exposed to the direct effects of solar heat and heat sources.
- ☞ exceed 60°C. It should be stored with a maximum of two pallets on top of each other.
- ☞ For more information, refer to the Material Safety Data Sheet (MSDS).